

Compact Rough Terrain Scissor

- » Compact diesel rough terrain scissor lifts.
- » Excellent rough terrain performance.
- » Easy to operate.
- » Roll-out deck extension for extra reach.

- » Ideal for outdoor work in confined spaces.
- » 4 wheel drive.
- » 4 hydraulic outriggers with automatic levelling.
- » Proportional joystick control.
- » Exclusive @ OMEGA 3 years warranty.

S2770RT/S3370RT Scissor Lift

Specifications

		S2770RT	S3370RT
Max. working height		10,23 m	12,1 M
Max. platform height	(A)	8,23 m	10,1 M
Platform capacity (SWL)		580 kg	450 kg
Platform size - stowed	(B)	2,71 m x 1,65 m	2,71 m x 1,65 m
Platform size - extended	(C)	3,9 m x 1,65 m	3,9 m x 1,65 m
Extension deck length		1,2 M	1,2 M
Overall width	(D)	1,8 m	1,8 m
Overall length	(E)	3,4 m	3,4 m
Stowed height	(F)	2,59 m	2,7 M
Weight		2800 kg	3620 kg
Max. drive height		8,23 m	10,1 m
Max. drive speed (stowed)		4,5 km/h	4,5 km/h
Max. drive speed (elevated)		0,5 km/h	0,3 km/h
Inside turning radius		2,44 m	2,44 m
Gradeability		25 %	25%
Ground clearance		33 cm	33 cm
Power source		Kubota D-902 water-cooled diesel 22.5hp	Kubota D-902 water-cooled diesel 22.5hp

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.





Standard **features**

- » Powerful diesel engine.
- » 4 wheel drive.
- » 4 hydraulic outriggers with automatic levelling.
- » Roll-out deck extension.
- » Exclusive @ OMEGA 3 years warranty.
- » Manual lowering valve.
- » 5 year structural warranty.



