

 **snorkel**

A46JE

Electric Boom Lift

- » Working height up to 16 m.
- » Direct DC drive parallel wired wheel motors
- » Multi-function proportional controls.
- » Power line to platform.
- » Zero tailswing.
- » Hour meter & on-board diagnostics display.
- » Standard non-marking tyres.
- » Efficient direct electric drive.

A46JE Electric Boom

Specifications

	A46JE	A46T	A46RT
Max. working height	16,1 m	16,1 m	16,3 m
Max. platform height	14,1 m	14,1 m	14,3 m
Platform capacity (SWL)	227 kg	227 kg	227 kg
Max. working outreach	7,4 m	7,4 m	7,4 m
Overall width (A)	1,70 m	1,75 m	2,0 m
Overall length (C)	5,6 m	5,6 m	5,6 m
Stowed height (B)	2,0 m	2,0 m	2,1 m
Weight	6850 kg	6486 kg	6622 kg
Ground clearance	15,20 cm	15,2 cm	33 cm
Max. drive height	16,1 m	16,1 m	16,3 m
Max. drive speed (stowed)	5,1 km/h	5,1 km/h	7,2 km/h
Max. drive speed (elevated)	1,3 km/h	1,3 km/h	1,2 km/h
Turret rotation (non continuous)	360 degree	360 degree	360 degree
Gradeability	30%	30 %	45%
Inside turning radius	0,60 m	0,60 m	0,80 m
Power source	8x 6 V - 360 Ah Batteries	8 x 6v 360Ah batteries	Kubota V1505T Diesel

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Proportional one hand control
- » Ultra-tight inside turning radius
- » Power cable to platform
- » Integrated battery charger (DC)
- » Exclusive @ OMEGA - 3 years warranty
- » Ground control station
- » CE approved
- » On board diagnostic display
- » Direct DC drive parallel wired wheel motors
- » 5 year structural warranty



WORKING ENVELOPE

