



snorkel

TB47J



Telescopic Boom Lift

- » 150 degrees hydraulic platform rotation.
- » 360 degrees continuous turntable rotation.
- » Proportional drive, lift and swing.
- » Driveable at full height.
- » Power line to platform.
- » Dual lanyard attachment points.
- » Rheostat control for jib, extend & platform level.
- » 5 degrees tilt alarm.

TB47J Telescopic Boom Lift

Specifications

		TB47J
Max. working height		16,2 m
Max. platform height	(A)	14,2 m
Platform size (stowed)		1,52 m x 0,76 m
Platform capacity (SWL)		227 kg
Stowed length	(C)	8,2 m
Stowed height	(D)	2,4 m
Width	(B)	2,4 m
Ground clearance		25 cm
Weight		6123 kg
Max. drive speed stowed		4,8 km/h
Power source		Kubota 59hp Tier 4i Flex V2403 Turbo Diesel

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Driveable at full height.
- » Proportional drive, lift and swing.
- » Drive motion alarm.
- » Flashing amber light.
- » Horn.
- » Operators manual.
- » Ansi compliant.



WORKING ENVELOPE

