

 **snorkel**

TB50

Telescopic Boom Lift

- » Driveable at full height.
- » Tilt alarm.
- » 125 volt GFCI AC outlet.
- » Aluminum upper booms.
- » Hour meter.
- » High engine temp/low oil pressure shut down.
- » Lifting lugs.
- » Hydraulic oil level/temp gauges.

TB50 Telescopic Boom Lift

Specifications

		TB50
Max. working height		17,4 m
Max. platform height	(A)	15,4 m
Horizontal reach		11,9 m
Platform size (stowed)		76 cm x 152 cm
Platform capacity (SWL)		227 kg
Stowed length	(C)	7,7 m
Stowed height	(D)	2,4 m
Width	(B)	2,4 m
Ground clearance		25 cm
Gradeability		4,0%
Weight		6123 kg
Max. drive speed stowed		4,8 km/h
Max. drive speed elevated		1,6 km/h
Power source	Kubota 59hp Tier 4i Flex V2403 Turbo Diesel	

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » 360 degree continuous turntable rotation.
- » Proportional drive, lift & swing.
- » Engine anti-restart.
- » Tie down lugs.
- » 180 degree hydraulic platform rotation.
- » 12 Volt emergency operated power.
- » Manual bleed down valve.

