

 **snorkel**

TB60RT
TB66JRT

Telescopic Boom Lift

- » Proportional drive, boom lift and swing.
- » Two safety lanyard attachments.
- » Driveable at full height.
- » High grip, foam filled lug tires.
- » Rheostat control for jib, extend & platform level.
- » Power line to platform.
- » Operators manual.
- » ANSI compliant.

TB60RT/TB66JRT Telescopic Boom Lift

Specifications

	TB60RT	TB66JRT
Max. working height	20,3 m	21,1 m
Max. platform height	18,3 m	20,1 m
Horizontal reach	15,2 m	17,1 m
Platform size (stowed)	2,44 m x 0,76 m	2,44 m x 0,76 m
Platform capacity (SWL)	227 kg	227 kg
Overall length (B)	9,4 m	10 m
Stowed height (C)	2,7 m	2,7 m
Overall width (A)	2,5 m	2,5 m
Ground clearance	33 cm	33 cm
Gradeability	30 %	30 %
Weight	9857 kg	11916 kg
Max. drive speed stowed	4,8 km/h	4,8 km/h
Max. drive speed elevated	0,8 km/h	0,96 km/h
Power source	Deutz F4L-2011F air cooled diesel	Deutz F4L-2011F air cooled diesel

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » 150 degree hydraulic platform rotation.
- » 360 degree continuous turntable rotation.
- » Drive motion alarm.
- » Flashing amber light.
- » High grip foam filled lug tires.
- » Proportional drive, boom lift and swing.
- » ANSI compliant.



WORKING ENVELOPE

