

 **snorkel**

TB85J

Telescopic Boom Lift

- » Proportional drive, boom lift, swing and extend.
- » Two safety lanyard attachments.
- » Driveable at full height.
- » High grip, foam filled lug tires.
- » Rheostat control for jib, platform level & platform rotate.
- » Power line to platform.
- » Operators manual.
- » ANSI compliant.

TB85J Telescopic Boom Lift

Specifications

		TB85J
Max. working height		26,2 m
Max. platform height		24,2 m
Horizontal reach		21,7 m
Platform size (stowed)		2,44 m x 0,61 m
Platform capacity (SWL)		227 kg
Overall length	(B)	11,82 m
Stowed height	(C)	2,93 m
Overall width	(A)	2,62 m
Ground clearance		9,4 cm
Gradeability		40 %
Weight		13925 kg
Max. drive speed stowed		4,8 km/h
Max. drive speed elevated		1,6 km/h
Power source		Kubota 59HP Tier 4i Flex v2403 Turbo Diesel

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » 150 degree hydraulic platform rotation.
- » 360 degree continuous turntable rotation.
- » Drive motion alarm.
- » Flashing amber light.
- » High grip foam filled lug tires.
- » Proportional drive, boom lift and swing.
- » ANSI compliant.



WORKING ENVELOPE

