

Articulated Boom Lift

- » Working height up to 28 m.
- » Hydraulic powered platform rotation.
- » Driveable at full height.
- » 4 wheel drive.

- » Proportional control of drive, boom lift and slew.
- » Foam filled lug tires.
- » Operator horn.
- » 4 wheel steer.

AB85RJ Articulated Boom Lift

Specifications

	AB85RJ
	Abookj
Max. working height	28 m
Max. platform height	26 m
Horizontal reach	18,9 m
Platform size (stowed)	0,91 m x 2,44 m
Platform capacity (SWL)	227 kg
Overall length (A)	13 M
Stowed height (B)	3 m
Overall width	2,6 m
Ground clearance	33 cm
Gradeability	45 %
Weight	17735 kg
Inside turning radius	2,94 m
Max. drive speed (stowed)	4,8 km/h
Power source	Deutz F4L-2011 (64hp) air cooled engine

Specifications subject to change without notice. Photos and diagrams in this brochure are for $% \left(1\right) =\left(1\right) \left(1\right) \left$ promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

25 20 10 dimensions in metres

Standard features

- » 2,4 m, 90 degree jib with 140 degree rotation.
- » Hydraulic powered platform rotation.
- » Driveable at full height.
- » Extra finger protection handrail.
- » High grip foam filled lug tires.
- » Proportional drive, boom lift and swing.
- » 4 wheel drive and steer.



