

JLG

660SJ

Telescopic Boom Lift

- » Working height up to 22 m.
- » Improved controls for a smoother movement and operator comfort.
- » Oscillating axle voor superb terrain performance.
- » Workstation in the Sky accessory options available to help you get the job done.
- » Horizontal outreach up to 17 m.
- » 4 wheel drive.

660SJ Telescopic Boom Lift

Specifications

	660SJ
Max. working height	22,31 m
Max. platform height	20,31 m
Horizontal reach	17,30 m
Platform size (stowed)	0,91 m x 2,44 m
Platform capacity (SWL)	230 kg
Overall length	10,21 m
Stowed height	2,57 m
Overall width	2,49 m
Ground clearance	30 cm
Gradeability	45 %
Weight	13150 kg
Outside turning radius (4wd)	2,89 m
Max. drive speed (4wd)	6,8 km/h
Power source	Deutz D2011Lo4 26.4 kW 49pk

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Horizontal outreach up to 17 m.
- » Workstation in the Sky accessory options available to help you get the job done.
- » Oscillating axle voor superb terrain performance.
- » Improved controls for a smoother movement and operator comfort.
- » 4 wheel drive.

