



400TS
SERIES

Track scissor with levelling capabilities

- » Up to 10,5 m working height.
- » Standard double extension decks - up to 5 m extended.
- » Easy levelling capabilities, side - side / fore - aft.
- » Full electric drive system
- » All electrical, hydraulic are in closed compartments.
- » Guardrails are easily detachable.
- » Fully proportional drive control, with double joystick controllers.

OMEGASOLUTIONS.BIZ

400TS-series Track scissor

Specifications

| | 405TS | 408TS |
|--------------------------------|--|--------------|
| Max. working height | 10,5 m | 10,5 m |
| Max. platform height | 8,5 m | 8,5 m |
| Stowed height (top guardrails) | 2,9 m | 2,9 m |
| Stowed height (rails detached) | 2,0 m | 2,0 m |
| Width | 1,6 m | 1,6 m |
| Length - stowed | 3,0 m | 3,0 m |
| Track length | 2,65 m | 2,65 m |
| Track base | 1,6 m | 1,6 m |
| Ground clearance | 33 cm | 33 cm |
| Platform length - retracted | 3,0 m | 3,0 m |
| Platform length - extended | 5,0 m | 5,0 m |
| Lifting capacity | 500 kg | 800 kg |
| Max. load roll-out decks | 250 kg | 250 kg |
| Drive speed stowed | 2,5 km/h | 2,5 km/h |
| Gradeability | 40% | 40% |
| Weight | 4.400 kg | 4.600 kg |
| Engine | Kubota V1505 | Kubota V1505 |
| Levelling capabilities | 5 degrees side / side 6 degrees rear / front Controls by manual - and by Auto-levelling feature | |

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.



AIR-LINK REMOTE

FIXED UPPER CONTROLS



WWW.OMEGASOLUTIONS.BIZ

Standard features

- » Up to 10,5 m working height.
- » Auto and manual levelling.
- » Removable upper controls.
- » Double extension decks.
- » Fully proportional drive and lift control.
- » Easy maintenance access to mechanical, electrical and diesel components without raising platform or swinging out trays.
- » CE compliant / CSA compliant
- » Power full diesel engine - Kubota V1105.
- » On-Board diagnostic system.



Optional features

- » DC / AC convertor for 220Vac supply, up to 1,5 kW.
- » Non-marking tracks.
- » Custom colours.
- » Radiographic remote control - **Air-Link**.

Leemidden 21
2678 ME De Lier
The Netherlands



+ 31 174 - 525 990
solutions@omegagroup.eu