

snorkel

UL SERIES

Personnel Lifts

- » Patented Girder Lock telescopic mast system.
- » Integrated tilt-back system.
- » Ground level entry.
- » EZ loader system for transport.
- » Outrigger interlock indicators.
- » Integrated battery charger (DC only).
- » Non-marking wheels and casters.
- » CE approved.

UL Series Personnel lifts

Specifications

	UL 25	UL 30	UL 40
Max. working height	9,60 m	11,70 m	14,10 m
Max. platform height (A)	7,60 m	9,70 m	12,10 m
Platform capacity	159 kg	136 kg	136 kg
Outrigger footprint (BxC)	2,06 m x 1,99 m	2,06 m x 1,99 m	2,95 m x 2,85 m
Overall width (F)	0,74 m	0,74 m	0,74 m
Overall length (D)	1,26 m	1,32 m	1,32 m
Overall height (E)	1,99 m	2,51 m	2,90 m
Weight	390 kg (AC) 420 kg (DC)	435 kg (AC) 465 kg (DC)	470 kg (AC) 500 kg (DC)
Tilt back height (G)	1,95 m	1,95 m	2,00 m
Tilt back length (H)	2,60 m	2,64 m	2,99 m
Wall access	35,60 cm	35,60 cm	73,60 cm
Power source	120/220V AC 50HZ	120/220V AC 50HZ	120/220V AC 50HZ
Power source (optional)	1 x 12V 105AH battery	1 x 12V 105AH battery	1 x 12V 105AH battery

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Patented Girder Lock telescopic mast system.
- » Integrated tilt-back system.
- » Ground level entry.
- » EZ loader system for transport.
- » 3 years warranty.
- » Outrigger interlock indicators.
- » Integrated battery charger (DC only).
- » Non-marking wheels and casters.
- » CE approved.
- » 5 year structural warranty



OUTRIGGER FOOTPRINT

