

 **snorkel**

**S3215E**  
**S3219E**



## Electric Scissor Lifts

- » Roll-out deck extension with dual locks.
- » Swing-out service trays.
- » Saloon-door style entry gates.
- » 90 cm length roll-out deck extension.
- » Easy one-hand proportional controls.
- » Large, two person platform.
- » Easy one-hand proportional controls.
- » Hour meter & on-board diagnostics display.
- » Non-marking tires.
- » Exclusive @ OMEGA - 3 years warranty.

# S3215E / S3219E Scissor Lift

## Specifications

	S3215E	S3219E
Max. working height	6,6 m	7,8 m
Max. platform height <b>(A)</b>	4,60 m	5,8 m
Platform capacity (SWL)	272 kg	250 kg
Platform size - stowed	0,68 x 1,64 m	0,78 x 1,64 m
Platform size - extended	0,68 x 2,53 m	0,78 x 2,54 m
Extension deck length	0,89 m	0,9 m
Overall width <b>(D)</b>	0,81 m	0,81 m
Overall length <b>(C)</b>	1,74 m	1,78 m
Overall height <b>(B)</b>	1,91 m	2,00 m
Weight	1238 kg	1611 kg
Max. drive height	6,60 m	7,8 m
Max. drive speed (stowed)	3,20 km/h	3,2 km/h
Max. drive speed (elevated)	0,60 km/h	0,6 km/h
Inside turning radius	0,10 m	0,1 m
Gradeability	25%	25%
Ground clearance	6,40 cm	6,60 cm
Power source	24V DC battery electric	4 x 6 V - 220 Ah Batteries

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.



Swing-out service trays - for easy access for maintenance and service.

## Standard features

- » Proportional one hand control.
- » Ultra-tight inside turning radius.
- » Fully proportional controls, as well for drive and lift functions.
- » Forklift pockets.
- » Exclusive @ OMEGA - 3 years warranty.
- » Ground control station.
- » Swing-out service trays.
- » On board diagnostic display.
- » 2 persons + equipment capacity indoors.
- » 1 person + equipment capacity outdoor.
- » 5 year structural warranty

