



 **snorkel**

S4726E
S4732E

Electric Scissor Lift

- » Roll-out deck extension with dual locks.
- » Non-marking tyres.
- » Loading control pendant.
- » Swing-out service trays.
- » Saloon-door style entry gates.
- » Ultra tight inside turning radius.
- » Motion alarm.
- » Exclusive @ OMEGA - 3 years warranty.

S4726E/S4732E Scissor Lift

Specifications

	S4726E	S4732E
Max. working height	9,90 m	11,80 m
Max. platform height (A)	7,90 m	9,80 m
Platform size (stowed)	2,14 m x 1,05 m	2,14 m x 1,05 m
Platform capacity	454 kg	350 kg
Extension deck length (B)	1,21 m	1,21 m
Overall length (with step) (D)	2,30 m	2,30 m
Weight	1993 kg	2630 kg
Overall width (C)	1,19 m	1,19 m
Stowed height (E)	2,30 m	2,39 m
Max. drive height	7,90 m	9,80 m
Max. drive speed (stowed)	3,20 km/h	3,20 km/h
Max. drive speed (elevated)	0,60 km/h	0,60 km/h
Inside turning radius	0,25 m	0,25 m
Outside turning radius	2,31 m	2,31 m
Gradeability	25%	25%
Ground clearance	7,60 cm	7,60 cm
Power source	24V DC battery electric	24V DC battery electric

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Roll-out deck extension with dual locks.
- » Dual lanyard attachment points.
- » CE approved.
- » Integrated battery charger.
- » Exclusive @ OMEGA - 3 years warranty.
- » Saloon-door style entry gates.
- » Proportional controls including descent.
- » Hour meter & onboard diagnostics display.
- » 2 persons + equipment capacity indoor.
- » 1 person + equipment capacity outdoor.
- » 5 year structural warranty



TURNING RADIUS

