



 **snorkel**

S3220E
S3226E

Electric Scissor Lift

- » Roll-out deck extension with dual locks.
- » Loading control pendant.
- » Swing-out service trays.
- » Easy one-hand proportional controls.
- » Saloon-door style entry gates.
- » Proportional controls, including descent.
- » Hour meter & on-board diagnostics display.
- » Power line to platform.

S3220E/S3226E Scissor

Specifications

		S3220E	S3226E
Max. working height		8,1 m	9,9 m
Max. platform height	(A)	6,1 m	7,9 m
Platform capacity (SWL)		408 jg	250 kg
Platform size - stowed		0,66 m x 2,18 m	0,66 m x 2,18 m
Platform size - extended		0,66 m x 3,09 m	0,66 m x 3,09 m
Extension deck length	(B)	0,91 m	0,91 m
Overall width	(C)	0,81 m	0,81 m
Overall length	(D)	2,26 m	2,26 m
Stowed height	(E)	2,11 m	2,30 m
Weight		2041 kg	2045 kg
Max. drive height		6,1 m	7,9 m
Max. drive speed (stowed)		3,2 km/h	3,20 km/h
Max. drive speed (elevated)		0,6 km/h	0,6 km/h
Inside turning radius		0,76 m	0,76 m
Gradeability		25 %	25%
Ground clearance		7,6 cm	7,6 cm
Power source		24V DC battery electric	24V DC battery electric

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Proportional controls, including descent.
- » Ultra-tight inside turning radius.
- » Fully proportional controls, as well for drive and lift functions.
- » Forklift pockets.
- » Exclusive @ OMEGA - 3 years warranty.
- » Ground control station.
- » Swing-out service trays.
- » On board diagnostic display.
- » 2 persons + equipment capacity indoors.
- » 1 person + equipment capacity outdoor.
- » 5 year structural warranty



TURNING RADIUS

