

 **snorkel**

A38E

Articulated Boom Lift

- » Working height up to 13,5 m.
- » Excellent up and over ability with 6,1 m working outreach at 5,4 m clearance height.
- » Ultra-tight inside turning radius.
- » Direct DC drive parallel wired wheel motors.
- » Leading class electric articulated boom lift.
- » Easy one-hand proportional controls.
- » Standard non-marking tyres.
- » Suitable for indoor and outdoor use.
- » Exclusive @ OMEGA - 3 years warranty.

A38E Articulated Boom

Specifications

	A38E
Max. working height	13,5 m
Max. platform height	11,5 m
Platform capacity (SWL)	215 kg
Max. working outreach	6,1 m
Overall width	1,5 m
Stowed length	4,04 m
Stowed height	2,0 m
Weight	3.770 kg
Ground clearance	12 cm
Max. drive height	13,5 m
Max. drive speed (stowed)	4 km/h
Max. drive speed (elevated)	0,7 km/h
Turret rotation (non continuous)	360 degrees
Gradeability	36%
Inside turning radius	0,4 m
Power source	8x 6 V - 220 Ah Batteries

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.



Standard features

- » Proportional one hand control
- » Ultra-tight inside turning radius
- » Power cable to platform
- » Integrated battery charger (DC)
- » Exclusive @ OMEGA - 3 years warranty
- » Ground control station
- » CE approved
- » On board diagnostic display
- » Direct DC drive parallel wired wheel motors
- » 5 year structural warranty

