



**OMEGA**

SALES

 **snorkel**

**A62JRT**

## Articulated Boom Lift

- » Working height up to 20,8 m.
- » Powerful hydrostatic 4 wheel drive.
- » Oscillating axle.
- » Zero tailswing.
- » Ultra-tight turning radius.
- » Swing-out engine tray.
- » Hour meter.
- » Motion alarm.

[www.omegasales.eu](http://www.omegasales.eu)

# A62JRT Articulated Boom Specifications

		A62JRT
Max. working height		20,8 m
Max. platform height		18,8 m
Platform capacity (SWL)		227 kg
Max. working outreach		11,1 m
Overall width	(A)	2,4 m
Overall length	(B)	8,6 m
Stowed height		2,6 m
Weight	(C)	10659 kg
Ground clearance		35 cm
Max. drive height		18,8 m
Max. drive speed (stowed)		6,1 km/h
Max. drive speed (elevated)		1,2 km/h
Turret rotation (non continuous)		360 degrees
Gradeability		45%
Inside turning radius		1,4 m
Power source		Kubota v2403M-T 44KW/59HP

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

## Standard features

- » Snorkel Guard secondary guarding system.
- » Powerful hydrostatic 4 wheel drive.
- » Oscillating axle.
- » Zero tailswing.
- » Ultra-tight turning radius.
- » Power line to platform.
- » CE approved.
- » DC emergency operation.
- » Tri-entry platform.
- » 2 year parts & labour, 5 year structural warranty



### WORKING ENVELOPE

