

Speed Level Sigma Lift

- » Up to 11 m working height.
- » Fast platform leveling on slopes, automatic or manual selection.
- » Up to 770 platform capacity.
- » Fully proportional drive and lift controls.

- » Quad-trax 4WD Power Package giving 40% gradeability.
- » Non-skid metal deck contsruction.
- » Eight 6V 370Ah industrial deep cycle batteries.
- » Easy maintenance access to mechanical and electrical components without raising platform or swining out trays.

84ES series Scissor Lift

Specifications

	2684ES	3084ES
Max. working height	9,75 m	11 m
Max. platform height	7,93 m	9 m
Max. drive height	7,93 m	9 m
Stowed height (top guardrails)	2,67 m	2,67 m
Stowed height (rails folded)	1,78 m	1,78 m
Length - stowed	3,8 m	4,4 m
Width	2,13 m	2,13 m
Platform length	3,65 m	4,26 m
Platform length extended	4,57 m	4,26 m
Platform width	1,83 m	=
Lift capacity	770 kg	680 kg
Extension deck capacity	227 kg	=
Drive speed stowed	4,8 km/h	4,8 km/h
Gradeability	40 %	40 %
Weight	3630 kg	3630 kg
Engine	(8) 6V 370Ah industrial deep- cycle	(8) 6V 370Ah industrial deep- cycle

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.





Standard features

- » Automatic and manual platform levelling,
- » Large sheet loading entrance accommodates1,22 m material.
- » Removable upper controls.
- » Fold down guardrails.
- » Lubrication-free bearings.
- » Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays.
- » CE compliant.
- » Power full diesel engine Kubota D1105.



Optional features

- » Flashing beacons (continuous)
- » Air line to platform.
- » Non-marking tires.
- Hydraulic powered generator 220Vac
- » Custom colours