



4069 SERIES

Electric Crossover Scissor Lift

- » Standard integrated sheet material rack designed and approved by the manufacturer.
- » Super-low platform entry height.
- » Roll-out deck extension with incremental locking positions.
- » Standard swing gate.
- » 110V power to platform.
- » Standard 4-wheel drive with Quad-Trax traction control.
- » Fully proportional drive and lift controls.
- » Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays.

4069 series Scissor Lift

Specifications

	4069RT	4069ERT
Max. working height	14 m	16 m
Max. platform height	12,2 m	12,2 m
Max. drive height	12,2 m	14 m
Stowed height (top guardrails)	2,5 m	2,5 m
Stowed height (rails folded)	1,98 m	1,98 m
Length - stowed	3,2 m	3,2 m
Width	1,75 m	1,75 m
Platform length	3 m	3 m
Platform length extended	4,22 m	4,22
Platform width	1,5 m	1,5 m
Lift capacity	360 kg	360 kg
Extension deck capacity	113 kg	113 kg
Drive speed stowed	6 km/h	6 km/h
Gradeability	40 %	40 %
Weight	4900 kg	4900 kg
Engine	48V DC, 375Ah battery pack Diesel	48V DC, 375Ah battery pack Electric

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate operators manual for detailed instructions on the proper use and maintenance.

Standard features

- » Lubrication-free scissor bearings.
- » Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays..
- » Logically grouped components and numbered wiring for easy reference.
- » Dedicated compartments protect electrical and hydraulic components.
- » Emergency shut-off at platform and lower controls.
- » CE approved.



Optional features

- » Flashing beacons (continuous)
- » Air line to platform.
- » Non-marking tires.
- » Diesel or electric
- » Custom colours

www.omegasales.eu

Leemidden 21
2678 ME De Lier
The Netherlands

+ 31 174 - 525 990
sales@omegasales.eu